

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1



Revision: 03.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Polytec TC 406 Part A
- **Article number:** TC406A
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Epoxy resin for thermally conductive adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Polytec PT GmbH
Ettlinger Str. 30
D- 76307 Karlsbad
GERMANY
E-Mail: info@polytec-pt.de
- **Further information obtainable from:**
Product Safety
Tel. +49-(0)7243-6044000
info@polytec-pt.de
- **1.4 Emergency telephone number:**
Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
This mixture is classified as hazardous according to regulation (EC) 1272 / 2008 (CLP)
- **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Muta. 2	H341 Suspected of causing genetic defects.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS07 GHS08
- **Signal word** Warning
- **Hazard-determining components of labelling:**
formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
1,4-bis(2,3-epoxypropoxy)butane
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1

Revision: 03.09.2021

Trade name: Polytec TC 406 Part A

(Contd. of page 1)

Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P321 Specific treatment (see on this label).
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain substances complying with criteria for PBT and vPvB according to regulation (EC) No. 1907/2006 (REACH) annex XIII respectively regulation (EU) No. 253/2011.

- **PBT:** not applicable
- **vPvB:** not applicable

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 9003-36-5 Reg.nr.: 01-2119454392-40-0000	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-10%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-10%
CAS: 5026-74-4 Reg.nr.: 01-2119954405-36-0000	p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline ⚠ Muta. 2, H341; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-10%
CAS: 2425-79-8 EINECS: 219-371-7 Index number: 603-072-00-7 Reg.nr.: 01-2119494060-45-0000	1,4-bis(2,3-epoxypropoxy)butane ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1

Revision: 03.09.2021

Trade name: Polytec TC 406 Part A

(Contd. of page 2)

- **After swallowing:** Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Do not breathe fumes. Avoid contact with eyes, skin and clothing
- **Information about fire - and explosion protection:**
Keep respiratory protective device available.
No special measures required
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Keep container tightly closed and store at room temperature. Ensure good ventilation
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1

Revision: 03.09.2021

Trade name: Polytec TC 406 Part A

(Contd. of page 3)

- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs**

9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	DNEL oral long term exposure - systemic effect	60.25 mg/kg bw/day (general population)
Dermal	DNEL dermal long term exposure	62.5 mg/kg bw/day (general population) 104.15 mg/kg bw/day (worker)
Inhalative	DNEL Long term exposure - systemic effect	8.7 mg/m ³ (general population) 29.39 mg/m ³ (worker)

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral	DNEL oral long term exposure - systemic effect	0.75 mg/kg bw/day (worker)
Dermal	DNEL dermal long term exposure	8.33 mg/kg bw/day (worker)
Inhalative	DNEL Acute/short term exposure - local effect	12.25 mg/m ³ (worker)
	DNEL Long term exposure - systemic effect	12.25 mg/m ³ (worker)

5026-74-4 p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline

Dermal	DNEL dermal long term exposure	0.26 mg/kg bw/day (worker)
Inhalative	DNEL Acute/short term exposure - local effect	56 mg/m ³ (worker)
	DNEL Long term exposure - systemic effect	1.86 mg/m ³ (worker)

2425-79-8 1,4-bis(2,3-epoxypropoxy)butane

Oral	DNEL oral long term exposure - systemic effect	0.33 mg/kg bw/day (general population)
Dermal	DNEL dermal long term exposure	3.33 mg/kg bw/day (general population) 6.66 mg/kg bw/day (worker)
Inhalative	DNEL Long term exposure - systemic effect	1.16 mg/m ³ (general population) 4.7 mg/m ³ (worker)

- **PNECs**

9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

PNEC aqua	0.003 mg/l (fresh w) (freshwater)
PNEC aqua	0.0003 mg/l (marine w) (marine water)
PNEC sediment	0.294 mg/kg (fresh w) (freshwater)

2425-79-8 1,4-bis(2,3-epoxypropoxy)butane

PNEC aqua	0.024 mg/l (fresh w) (freshwater)
PNEC aqua	0.0024 mg/l (marine w) (marine water)
PNEC sediment	0.084 mg/kg (fresh w) (freshwater)

- **Additional information:** The lists valid during the making were used as basis.

- 8.2 Exposure controls

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1

Revision: 03.09.2021

Trade name: Polytec TC 406 Part A

(Contd. of page 4)

Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when aerosol or mist is formed.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Gloves made from the following material(s) are recommended: Butyl rubber minimum thickness 0,5mm.

Alternative glove material: Nitrile rubber (thickness: 0,4 mm)

Examinations according DIN EN 374-2 have to be following result: It must be achieved a protection index of at least grade 2 in 3 test chemicals in Annex A to EN 374-3. Please ask your manufacturer of gloves or visit www.gisbau.de/service/epoxi/expotab.html for more information.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The penetration time of the glove material should be longer than 8 hours (Thickness: butyl rubber 0,5mm ; nitrile rubber 0,35mm)

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Pasty
· Colour:	White
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value:	Not determined.
--------------------	-----------------

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	Undetermined.

· Flash point:	Not applicable.
-----------------------	-----------------

· Flammability (solid, gas):	Not applicable.
-------------------------------------	-----------------

· Decomposition temperature:	Not determined.
-------------------------------------	-----------------

· Auto-ignition temperature:	Product is not selfigniting.
-------------------------------------	------------------------------

· Explosive properties:	Product does not present an explosion hazard.
--------------------------------	---

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1

Revision: 03.09.2021

Trade name: Polytec TC 406 Part A

(Contd. of page 5)

· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.9 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 23 °C:	200,000 mPas
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Strong oxidizing and reducing compounds, strong acids and alkali
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	LD50	>10,000 mg/kg (rat)
------	------	---------------------

Dermal	LD50	>2,000 mg/kg (rat)
--------	------	--------------------

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	>15,000 mg/kg (rat)
------	------	---------------------

Dermal	LD50	23,000 mg/kg (rabbit)
--------	------	-----------------------

5026-74-4 p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline

Oral	LD50	2,739 mg/kg (rat)
------	------	-------------------

2425-79-8 1,4-bis(2,3-epoxypropoxy)butane

Oral	LD50	1,163 mg/kg (rat)
------	------	-------------------

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1

Revision: 03.09.2021

Trade name: Polytec TC 406 Part A

(Contd. of page 6)

Dermal LD50 >2,150 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity**
Suspected of causing genetic defects.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

EC50	220 mg/kg (Alg)
EC50/48h	2.8 mg/l (daphnia magna)
LC50/96h	3.6 mg/l (leu)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
This mixture does not contain substances complying with criteria for PBT or vPvB according to regulation (EC) No. 1907/2006 (REACH), annex XIII and regulation (EU) No. 253/2011.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1

Revision: 03.09.2021

Trade name: Polytec TC 406 Part A

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|-----------------|
| · 14.1 UN-Number
· ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name
· ADR, ADN, IMDG, IATA | -
Void |
| · 14.3 Transport hazard class(es)
· ADR, ADN, IMDG, IATA
· Class | Void |
| · 14.4 Packing group
· ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards:
· Marine pollutant: | Yes |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients are listed
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 1

Revision: 03.09.2021

Trade name: Polytec TC 406 Part A

(Contd. of page 8)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H341 Suspected of causing genetic defects.
- H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Health & Safety**· Contact:**

- Product Safety
- +49 (0)7243 604-4000 (during business hours)
- email: info@polytec-pt.de

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Muta. 2: Germ cell mutagenicity – Category 2
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3